

Loeering Versatile Track Sytem - VTS Specifications

10/17/2007 10:18:26 AM

VTS Part Number	HP	Track length	Wheel Base (in)	Standard Machine MPH	VTS MPH	Machine Weight	1 side unit weight	Total machine weight with tracks	PSI - Complete loader and Track	Ground Contact length Per Side (in)	Track Width (in)	Overall Machine width with VTS (in)	Ground Contact Area Per Side (sq in)	Up Stop	Spacers	Notes / Additional Hardware	
Bobcat																	
863	600683	73.5	56	43.7	7.2 / 12.5	5.7 / 10	7045	1555	9795	4.17	66.37	17.7	77	1,174.75	1	0	
873	600636	73	60	48.8	7.2 / 12.5	5.7 / 10	7285	1600	10125	3.98	71.87	17.7	86	1,272.10	1	0	
883	600636	73	60	48.8	7.2 / 12.5	5.7 / 10	8760	1600	11600	4.56	71.87	17.7	86	1,272.10	1	0	
S130	600946	46	50	35.4	7.3 / 0	6.3 / 0	5063	1135	6993	4.81	57.66	12.6	69	726.52	0	0	
S130	600949	46	50	35.4	7.3 / 0	6.3 / 0	5063	1246	7215	4.26	57.66	14.7	73	847.60	0	SN2302-8.0-1	9
S150	600935	46	52	40.6	7.3 / 0	6.3 / 0	5662	1145	7612	4.86	62.16	12.6	70	783.22	2	0	
S150	600973	46	52	40.6	7.3 / 0	6.3 / 0	5662	1200	7722	4.23	62.16	14.7	72	913.75	2	0	
S160	600935	56	52	40.6	7.3 / 0	6.3 / 0	5752	1145	7702	4.92	62.16	12.6	70	783.22	2	0	
S160	600973	56	52	40.6	7.3 / 0	6.3 / 0	5752	1200	7812	4.27	62.16	14.7	72	913.75	2	0	
S175	600935	46	52	40.6	7 / 0	6 / 0	5808	1145	7758	4.95	62.16	12.6	70	783.22	2	0	
S175	600973	46	52	40.6	7 / 0	6 / 0	5808	1200	7868	4.31	62.16	14.7	72	913.75	2	0	
S185	600935	56	52	40.6	7 / 0	6 / 0	5808	1145	7758	4.95	62.16	12.6	70	783.22	2	0	
S185	600973	56	52	40.6	7 / 0	6 / 0	5808	1200	7868	4.31	62.16	14.7	72	913.75	2	0	
S205	600935	61	52	40.6	7 / 0	6 / 0	6242	1145	8192	5.23	62.16	12.6	70	783.22	2	0	
S205	600973	61	52	40.6	7 / 0	6 / 0	6242	1200	8302	4.54	62.16	14.7	72	913.75	2	0	
S220	600724	73	60	48.8	6.9 / 12	5.5 / 9.6	7483	1672	10467	4.03	73.37	17.7	83	1,298.65	2	SN6302-8.0-1	
S220K	601197	73	60	48.3	6.9 / 12	5.5 / 9.6	7483	1672	10467	4.06	72.87	17.7	83	1,289.80	2	SN6302-8.0-1	
S250	600724	73	60	48.8	6.9 / 12	5.5 / 9.6	7483	1672	10467	4.03	73.37	17.7	83	1,298.65	2	SN6302-8.0-1	
S250	600724	73	60	48.8	6.9 / 12	5.5 / 9.6	7825	1672	10809	4.16	73.37	17.7	83	1,298.65	2	SN6302-8.0-1	
S250K	601197	73	60	48.3	6.9 / 12	5.5 / 9.6	7483	1672	10467	4.06	72.87	17.7	83	1,289.80	2	SN6302-8.0-1	
S250K	601197	73	60	48.3	6.9 / 12	5.5 / 9.6	7825	1672	10809	4.19	72.87	17.7	83	1,289.80	2	SN6302-8.0-1	
S300	600724	81	60	48.8	6.9 / 12	5.5 / 9.6	7483	1672	10467	4.03	73.37	17.7	83	1,298.65	2	SN6302-8.0-1	
S300	600724	81	60	48.8	6.9 / 12	5.5 / 9.6	8448	1672	11432	4.40	73.37	17.7	83	1,298.65	2	SN6302-8.0-1	
S300K	601197	81	60	48.3	6.9 / 12	5.5 / 9.6	7483	1672	10467	4.06	72.87	17.7	83	1,289.80	2	SN6302-8.0-1	
S300K	601197	81	60	48.3	6.9 / 12	5.5 / 9.6	8448	1672	11432	4.43	72.87	17.7	83	1,289.80	2	SN6302-8.0-1	
S330	601197	81	60	48.3	7.6 / 12.7	5.5 / 9.2	8448	1672	11432	4.43	72.87	17.7	83	1,289.80	2	SN6302-8.0-1	
S330	601197	81	60	48.3	6.9 / 12	5.5 / 9.6	7483	1672	10467	4.06	72.87	17.7	83	1,289.80	2	SN6302-8.0-1	
Case																	
1845C	600976	57	52	40.5	6 / 0	4.8 / 0	6185	1145	8135	5.19	62.16	12.6	75.5	783.22	1	0	
1845C	600979	57	52	40.5	6 / 0	4.8 / 0	6185	1200	8245	4.51	62.16	14.7	77.5	913.75	1	0	
40 XT	600985	57	54	41.2	6.8 / 0	5.8 / 0	5716	1155	7686	4.83	63.16	12.6	73	795.82	0	0	
40 XT	600991	57	54	41.2	6.8 / 0	5.8 / 0	5716	1210	7796	4.20	63.16	14.7	75	928.45	0	0	
410	600985	49	54	41	6.8 / 0	5.8 / 0	5500	1155	7470	4.69	63.16	12.6	73	795.82	0	0	
410	600991	49	54	41	6.8 / 0	5.8 / 0	5500	1210	7580	4.08	63.16	14.7	75	928.45	0	0	
420	600985	56	54	41	6.8 / 0	5.8 / 0	5813	1155	7783	4.89	63.16	12.6	73	795.82	0	0	
420	600991	56	54	41	6.8 / 0	5.8 / 0	5813	1210	7893	4.25	63.16	14.7	75	928.45	0	0	
430	601000	74	54	43.1	7 / 0	5.6 / 0	6875	1155	8845	5.39	65.16	12.6	74.5	821.02	0	0	
430	601000	75	54	43.1	7 / 0	5.6 / 0	6562	1155	8512	5.18	65.16	12.6	74.5	821.02	0	0	
430	601006	74	54	43.1	7 / 0	5.6 / 0	6875	1210	8955	4.67	65.16	14.7	76.5	957.85	0	0	
430	601006	75	54	43.1	7 / 0	5.6 / 0	6562	1210	8622	4.50	65.16	14.7	76.5	957.85	0	0	
430	600621	74	56	43.1	7 / 0	5.6 / 0	6875	1555	9645	4.11	66.37	17.7	79.5	1,174.75	1	0	
430	600621	75	56	43.1	7 / 0	5.6 / 0	6562	1555	9312	3.96	66.37	17.7	79.5	1,174.75	1	0	
435	600627	75	58	44.9	7.2 / 0	5.7 / 0	6700	1570	9480	3.89	68.87	17.7	88	1,219.00	1	0	
440	601000	82	54	43.1	7 / 0	5.6 / 0	7000	1155	8970	5.46	65.16	12.6	74.5	821.02	0	0	
440	601000	85	54	43.1	7 / 0	5.6 / 0	6906	1155	8856	5.39	65.16	12.6	74.5	821.02	0	0	
440	601006	82	54	43.1	7 / 0	5.6 / 0	7000	1210	9080	4.74	65.16	14.7	76.5	957.85	0	0	
440	601006	85	54	43.1	7 / 0	5.6 / 0	6906	1210	8966	4.68	65.16	14.7	76.5	957.85	0	0	
440	600621	82	56	43.1	7 / 0	5.6 / 0	7000	1555	9770	4.16	66.37	17.7	79.5	1,174.75	1	0	
440	600621	85	56	43.1	7 / 0	5.6 / 0	6906	1555	9656	4.11	66.37	17.7	79.5	1,174.75	1	0	
445	600627	75	58	44.9	7.2 / 0	5.7 / 0	6700	1570	9480	3.89	68.87	17.7	88	1,219.00	1	0	
450	600630	85	58	46.4	7.1 / 11.1	5.7 / 8.8	8950	1570	11730	4.74	69.87	17.7	88	1,236.70	1	0	6
465	600642	85	60	50.5	7.1 / 11.1	5.7 / 8.8	9050	1600	11890	4.52	74.37	17.7	88	1,316.35	1	0	6
60XT	601000	69	54	43.1	7 / 0	5.6 / 0	6562	1155	8532	5.20	65.16	12.6	74.5	821.02	0	0	
60XT	601000	75	54	43.1	7 / 0	5.6 / 0	6562	1155	8512	5.18	65.16	12.6	74.5	821.02	0	0	
60XT	601006	69	54	43.1	7 / 0	5.6 / 0	6562	1210	8642	4.51	65.16	14.7	76.5	957.85	0	0	
60XT	601006	75	54	43.1	7 / 0	5.6 / 0	6562	1210	8622	4.50	65.16	14.7	76.5	957.85	0	0	
60XT	600621	69	56	43.1	7 / 0	5.6 / 0	6562	1555	9332	3.97	66.37	17.7	79.5	1,174.75	1	0	
60XT	600621	75	56	43.1	7 / 0	5.6 / 0	6562	1555	9312	3.96	66.37	17.7	79.5	1,174.75	1	0	
70XT	601000	79	54	43.1	7 / 0	5.6 / 0	6906	1155	8876	5.41	65.16	12.6	74.5	821.02	0	0	
70XT	601000	85	54	43.1	7 / 0	5.6 / 0	6906	1155	8856	5.39	65.16	12.6	74.5	821.02	0	0	
70XT	601006	79	54	43.1	7 / 0	5.6 / 0	6906	1210	8986	4.69	65.16	14.7	76.5	957.85	0	0	
70XT	601006	85	54	43.1	7 / 0	5.6 / 0	6906	1210	8966	4.68	65.16	14.7	76.5	957.85	0	0	
70XT	600621	79	56	43.1	7 / 0	5.6 / 0	6906	1555	9676	4.12	66.37	17.7	79.5	1,174.75	1	0	
70XT	600621	85	56	43.1	7 / 0	5.6 / 0	6906	1555	9656	4.11	66.37	17.7	79.5	1,174.75	1	0	
75XT	600627	75	58	44.9	7.2 / 0	5.7 / 0	6700	1570	9480	3.89	68.87	17.7	88	1,219.00	1	0	
85XT	600627	75	58	44.9	7.2 / 0	5.7 / 0	6700	1570	9480	3.89	68.87	17.7	88	1,219.00	1	0	
90XT	600630	85	58	46.4	7.1 / 11.1	5.7 / 8.8	8950	1570	11730	4.74	69.87	17.7	88	1,236.70	1	0	6
95XT	600642	85	60	50.5	7.1 / 11.1	5.7 / 8.8	9050	1600	11890	4.52	74.37	17.7	88	1,316.35	1	0	6
Caterpillar																	
216	600964	49	52	39	6.9 / 0	5.9 / 0	5709	1217	7803	5.10	60.66	12.6	70	764.32	2	SN2302-8.0-1	1, 9
216	600967	49	52	39	6.9 / 0	5.9 / 0	5709	1272	7913	4.44	60.66	14.7	72	891.70	2	SN2302-8.0-1	1, 9
226	600964	57	52	39	6.9 / 0	5.9 / 0	5834	1217	7928	5.19	60.66	12.6	70	764.32	2	SN2302-8.0-1	1, 9
226	600967	57	52	39	6.9 / 0	5.9 / 0	5834	1272	8038	4.51	60.66	14.7	72	891.70	2	SN2302-8.0-1	1, 9
228	600964	57	52	39	6.9 / 0	5.9 / 0	5834	1217	7928	5.19	60.66	12.6	70	764.32	2	SN2302-8.0-1	1, 9
228	600967	57	52	39	6.9 / 0	5.9 / 0	5834	1272	8038	4.51	60.66	14.7	72	891.70	2	SN2302-8.0-1	1, 9
232	601000	50	54	43	7 / 0	6 / 0	6661	1155	8631	5.26</							

Loeering Versatile Track Sytem - VTS Specifications

10/17/2007 10:18:27 AM

VTS Part Number	HP	Track length	Wheel Base (in)	Standard Machine MPH	VTS MPH	Machine Weight	1 side unit weight	Total machine weight with tracks	PSI - Complete loader and Track	Ground Contact length Per Side (in)	Track Width (in)	Overall Machine width with VTS (in)	Ground Contact Area Per Side (sq in)	Up Stop	Spacers	Notes / Additional Hardware	
Caterpillar																	
232	601009	50	54	43	7 / 0	6 / 0	6661	1266	8853	4.62	65.16	14.7	73	957.85	2	SN2302-8.0-1	9
236	601015	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1165	8997	5.40	66.16	12.6	73	833.62	0	0	1
236	601015	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1165	8977	5.38	66.16	12.6	73	833.62	0	0	1
236	601012	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1276	9219	4.74	66.16	14.7	77	972.55	0	SN2302-8.0-1	1, 9
236	601012	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1276	9199	4.73	66.16	14.7	77	972.55	0	SN2302-8.0-1	1, 9
236	600687	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1555	9777	4.07	67.87	17.7	78	1,201.30	2	0	
236	600687	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1555	9757	4.06	67.87	17.7	78	1,201.30	2	0	
242	601000	57	54	43	7 / 0	5.6 / 0	6748	1155	8718	5.31	65.16	12.6	69	821.02	0	0	
242	601009	57	54	43	7 / 0	5.6 / 0	6748	1266	8940	4.67	65.16	14.7	73	957.85	2	SN2302-8.0-1	9
246	601015	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1165	8997	5.40	66.16	12.6	73	833.62	0	0	1
246	601015	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1165	8977	5.38	66.16	12.6	73	833.62	0	0	1
246	601012	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1276	9219	4.74	66.16	14.7	77	972.55	0	SN2302-8.0-1	1, 9
246	601012	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1276	9199	4.73	66.16	14.7	77	972.55	0	SN2302-8.0-1	1, 9
246	600687	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1555	9777	4.07	67.87	17.7	78	1,201.30	2	0	
246	600687	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1555	9757	4.06	67.87	17.7	78	1,201.30	2	0	
246C	601198	75	60	48.8	7.7 / 11.9	6.1 / 9.5	7566	1600	10406	4.06	72.37	17.7	78	1,280.95	1	0	
248	601015	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1165	8997	5.40	66.16	12.6	73	833.62	0	0	1
248	601015	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1165	8977	5.38	66.16	12.6	73	833.62	0	0	1
248	601012	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1276	9219	4.74	66.16	14.7	77	972.55	0	SN2302-8.0-1	1, 9
248	601012	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1276	9199	4.73	66.16	14.7	77	972.55	0	SN2302-8.0-1	1, 9
248	600687	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1555	9777	4.07	67.87	17.7	78	1,201.30	2	0	
248	600687	70	56	44.6	6.9 / 11.6	5.5 / 9.2	7007	1555	9757	4.06	67.87	17.7	78	1,201.30	2	0	
252	600434	70	59	48.4	6.9 / 11	5.5 / 8.8	7832	1590	10652	4.22	71.37	17.7	78	1,263.25	2	0	
256C	601198	84	60	48.8	7.7 / 11.9	6.1 / 9.5	7566	1600	10406	4.06	72.37	17.7	78	1,280.95	1	0	
262	600434	70	59	48.4	6.9 / 11	5.5 / 8.8	7832	1590	10652	4.22	71.37	17.7	78	1,263.25	2	0	
262C	601198	84	60	48.8	7.7 / 11.9	6.1 / 9.5	7566	1600	10406	4.06	72.37	17.7	78	1,280.95	1	0	
268B	600434	70	59	48.4	6.9 / 11	5.5 / 8.8	7832	1590	10652	4.22	71.37	17.7	78	1,263.25	2	0	
272C	601241	94	63	54.3	7.7 / 11.9	6.1 / 9.5	8292	1780	11472	4.19	77.37	17.7	78	1,369.45	1	0	
Daewoo																	
450 Plus	600994	65	54	41.8	7.4 / 0	5.9 / 0	6911	1155	8881	5.49	64.16	12.6	72	808.42	0	0	
450 Plus	600997	65	54	41.8	7.4 / 0	5.9 / 0	6911	1210	8991	4.77	64.16	14.7	74	943.15	0	0	
460 Plus	600994	65	54	41.8	7.4 / 0	5.9 / 0	7174	1155	9144	5.66	64.16	12.6	72	808.42	0	0	
460 Plus	600997	65	54	41.8	7.4 / 0	5.9 / 0	7174	1210	9254	4.91	64.16	14.7	74	943.15	0	0	
470 Plus	600994	75	54	41.8	7.4 / 0	5.9 / 0	7478	1155	9448	5.84	64.16	12.6	72	808.42	0	0	
470 Plus	600997	75	54	41.8	7.4 / 0	5.9 / 0	7478	1210	9558	5.07	64.16	14.7	74	943.15	0	0	
Gehl																	
4635	600952	44/57	50	37	8.4 / 0	7.2 / 0	6060	1135	7990	5.41	58.66	12.6	74	739.12	0	0	2
4635	600955	44/57	50	37	8.4 / 0	7.2 / 0	6060	1190	8100	4.70	58.66	14.7	76	862.30	0	0	2
4640	600958	46/60	52	37.5	8.1 / 0	7 / 0	6200	1145	8150	5.42	59.66	12.6	74	751.72	0	0	2
4640	600961	46/60	52	37.5	8.1 / 0	7 / 0	6200	1210	8280	4.72	59.66	14.7	76	877.00	0	0	2
4835	600985	57	54	41.1	8.4 / 0	7.2 / 0	6240	1155	8210	5.16	63.16	12.6	73	795.82	0	0	2
4835	600991	57	54	41.1	8.4 / 0	7.2 / 0	6240	1210	8320	4.48	63.16	14.7	75	928.45	0	0	2
4840	600994	60	54	41.5	8.1 / 11.4	7 / 9.8	6480	1155	8450	5.23	64.16	12.6	73	808.42	0	0	2
4840	600997	60	54	41.5	8.1 / 11.4	7 / 9.8	6480	1210	8560	4.54	64.16	14.7	75	943.15	0	0	2
5635	600994	60/80	54	42	8.5 / 12.5	6.8 / 10	6960	1155	8930	5.52	64.16	12.6	75	808.42	0	0	2
5635	600994	82	54	42.5	8.4 / 0	6.7 / 0	7380	1155	9330	5.77	64.16	12.6	75	808.42	0	0	2
5635	600997	60/80	54	42	8.5 / 12.5	6.8 / 10	6960	1210	9040	4.79	64.16	14.7	77	943.15	0	0	2
5635	600997	82	54	42.5	8.4 / 0	6.7 / 0	7380	1210	9440	5.00	64.16	14.7	77	943.15	0	0	2
5635	600621	60/80	56	42	8.5 / 12.5	6.8 / 10	6960	1555	9730	4.14	66.37	17.7	79	1,174.75	1	0	2
5635	600621	82	56	42.5	8.4 / 0	6.7 / 0	7380	1555	10130	4.31	66.37	17.7	79	1,174.75	1	0	2
5640	601000	80	54	42.5	8.4 / 0	6.7 / 0	7380	1155	9330	5.68	65.16	12.6	75	821.02	0	0	2
5640	601000	60/82	54	42.5	8.4 / 12.5	6.7 / 10	7380	1155	9350	5.69	65.16	12.6	75	821.02	0	0	2
5640	601006	80	54	42.5	8.4 / 0	6.7 / 0	7380	1210	9440	4.93	65.16	14.7	77	957.85	0	0	2
5640	601006	60/82	54	42.5	8.4 / 12.5	6.7 / 10	7380	1210	9460	4.94	65.16	14.7	77	957.85	0	0	2
5640	600621	80	56	42.5	8.4 / 0	6.7 / 0	7380	1555	10130	4.31	66.37	17.7	79	1,174.75	1	0	2
5640	600621	60/82	56	42.5	8.4 / 12.5	6.7 / 10	7380	1555	10150	4.32	66.37	17.7	79	1,174.75	1	0	2
6635	600689	82	58	48.4	8.4 / 12.5	6.7 / 10	7800	1570	10580	4.22	70.87	17.7	80	1,254.40	2	0	2
6640	600689	82	58	48.4	8.4 / 12.5	6.7 / 10	7800	1570	10580	4.22	70.87	17.7	80	1,254.40	2	0	2
7600	601241	86	63	54.3	6.5 / 11	4.7 / 8	10180	1780	13360	4.88	77.37	17.7	88	1,369.45	1	0	2, 7
7610	601253	86	63	55	6.5 / 11	4.7 / 8	10180	1780	13360	4.82	78.37	17.7	88	1,387.15	1	0	2, 7
7800	601241	86	63	54.3	6.5 / 11	4.7 / 8	10180	1780	13360	4.88	77.37	17.7	88	1,369.45	1	0	2, 7
7810	601253	115	63	55	7.5 / 13	5.4 / 9.4	10260	1780	13440	4.84	78.37	17.7	88	1,387.15	1	0	2, 7
John Deere																	
240	601022	48	54	42.3	6.8 / 0	5.8 / 0	6195	1155	8165	4.97	65.16	12.6	70	821.02	0	0	
240	601003	48	54	42.3	6.8 / 0	5.8 / 0	6195	1210	8275	4.32	65.16	14.7	72	957.85	0	0	
250	601022	61	54	42.3	6.8 / 0	5.4 / 0	6290	1155	8260	5.03	65.16	12.6	70	821.02	0	0	
250	601003	61	54	42.3	6.8 / 0	5.4 / 0	6290	1210	8370	4.37	65.16	14.7	72	957.85	0	0	
260	600633	69	58	48.3	7 / 12	5.6 / 9.6	8250	1570	11030	4.40	70.87	17.7	86	1,254.40	1	0	
270	600633	69	58	48.3	7 / 12	5.6 / 9.6	8250	1570	11030	4.40	70.87	17.7	86	1,254.40	1	0	
280	601198	85	60	48.6	7 / 12	5.6 / 9.6	8250	1600	11090	4.33	72.37	17.7	86	1,280.95	1	0	
280	601198	85	60	48.6	7 / 12	5.6 / 9.6	8500	1600	11340	4.43	72.37	17.7	86	1,280.95	1	0	
317	601022	57	54	42.3	6.8 / 0	5.8 / 0	6300	1155	8270	5.04	65.16	12.6	70	821.02	0	0	

Loeering Versatile Track Sytem - VTS Specifications

10/17/2007 10:18:27 AM

VTS Part Number	HP	Track length	Wheel Base (in)	Standard Machine MPH	VTS MPH	Machine Weight	1 side unit weight	Total machine weight with tracks	PSI - Complete loader and Track	Ground Contact length Per Side (in)	Track Width (in)	Overall Machine width with VTS (in)	Ground Contact Area Per Side (sq in)	Up Stop	Spacers	Notes / Additional Hardware	
John Deere																	
317	601003	57	54	42.3	6.8 / 0	5.8 / 0	6300	1210	8380	4.37	65.16	14.7	72	957.85	0	0	
320	601022	62	54	42.3	6.8 / 0	5.4 / 0	6435	1155	8405	5.12	65.16	12.6	70	821.02	0	0	
320	601003	62	54	42.3	6.8 / 0	5.4 / 0	6435	1210	8515	4.44	65.16	14.7	72	957.85	0	0	
325	600633	69	58	47.6	7 / 12	5.6 / 9.6	8250	1570	11030	4.40	70.87	17.7	86	1,254.40	1	0	
328	600633	69	58	47.6	7 / 12	5.6 / 9.6	8250	1570	11030	4.40	70.87	17.7	86	1,254.40	1	0	
332	601198	85	60	47.6	7 / 12	5.6 / 9.6	8250	1600	11090	4.33	72.37	17.7	86	1,280.95	1	0	
332	601198	85	60	48.6	7 / 12	5.6 / 9.6	8500	1600	11340	4.43	72.37	17.7	86	1,280.95	1	0	
8875	600636	67	60	48	7.2 / 11.6	5.7 / 9.2	7193	1600	10033	3.94	71.87	17.7	86	1,272.10	1	0	
Komatsu																	
SK1020	600630	70	58	45.7	6.5 / 10	5.2 / 8	7573	1570	10353	4.19	69.87	17.7	83	1,236.70	1	0	
SK818	600994	47	54	41.7	6.5 / 10	5.6 / 8.6	6402	1155	8372	5.18	64.16	12.6	71	808.42	0	0	
SK818	601180	47	54	41.7	6.5 / 10	5.6 / 8.6	6402	1266	8594	4.56	64.16	14.7	75	943.15	2	SN2302-8.0-1	9
SK820	600994	54	54	41.7	6.5 / 10	5.6 / 8.6	6402	1155	8372	5.18	64.16	12.6	71	808.42	0	0	
SK820	601180	54	54	41.7	6.5 / 10	5.6 / 8.6	6402	1266	8594	4.56	64.16	14.7	75	943.15	2	SN2302-8.0-1	9
Sk815	600994	47/54	54	41.7	6.5 / 10	5.6 / 8.6	6402	1155	8372	5.18	64.16	12.6	71	808.42	0	0	
Sk815	601180	47/54	54	41.7	6.5 / 10	5.6 / 8.6	6402	1266	8594	4.56	64.16	14.7	75	943.15	2	SN2302-8.0-1	9
Mustang																	
2040	600952	40	50	36.5	7 / 0	6 / 0	5300	1135	7230	4.89	58.66	12.6	71	739.12	0	0	2
2040	600955	40	50	36.5	7 / 0	6 / 0	5300	1190	7340	4.26	58.66	14.7	73	862.30	0	0	2
2042	600952	43	50	36.5	7 / 0	6 / 0	5300	1135	7230	4.89	58.66	12.6	71	739.12	0	0	2
2042	600952	43	50	36.7	7 / 0	6 / 0	5300	1135	7230	4.89	58.66	12.6	71	739.12	0	0	2
2042	600955	43	50	36.5	7 / 0	6 / 0	5300	1190	7340	4.26	58.66	14.7	73	862.30	0	0	2
2042	600955	43	50	36.7	7 / 0	6 / 0	5300	1190	7340	4.26	58.66	14.7	73	862.30	0	0	2
2044	600952	43	50	36.5	7 / 0	6 / 0	5600	1135	7530	5.09	58.66	12.6	71	739.12	0	0	2
2044	600952	43	50	36.7	7 / 0	6 / 0	5600	1135	7530	5.09	58.66	12.6	71	739.12	0	0	2
2044	600955	43	50	36.5	7 / 0	6 / 0	5600	1190	7640	4.43	58.66	14.7	73	862.30	0	0	2
2044	600955	43	50	36.7	7 / 0	6 / 0	5600	1190	7640	4.43	58.66	14.7	73	862.30	0	0	2
2050	600958	49	52	38.5	7 / 0	6 / 0	5950	1145	7900	5.25	59.66	12.6	73	751.72	0	0	2
2050	600961	49	52	38.5	7 / 0	6 / 0	5950	1200	8010	4.57	59.66	14.7	75	877.00	0	0	2
2054	600958	49	52	38.5	7.2 / 0	6.2 / 0	6050	1145	8000	5.32	59.66	12.6	73	751.72	0	0	2
2054	600961	49	52	38.5	7.2 / 0	6.2 / 0	6050	1200	8110	4.62	59.66	14.7	75	877.00	0	0	2
2060	601018	62	52	38.8	7 / 0	5.6 / 0	7000	1145	8950	5.85	60.66	12.6	73	764.32	0	0	2
2060	600970	62	52	38.8	7 / 0	5.6 / 0	7000	1200	9060	5.08	60.66	14.7	75	891.70	0	0	2
2066	601000	60	54	43	7.7 / 11.2	6.1 / 8.9	7480	1155	9450	5.76	65.16	12.6	75	821.02	0	0	2
2066	601000	80	54	43	7.7 / 11.2	6.1 / 8.9	7480	1155	9430	5.74	65.16	12.6	75	821.02	0	0	2
2066	601006	60	54	43	7.7 / 11.2	6.1 / 8.9	7480	1210	9560	4.99	65.16	14.7	77	957.85	0	0	2
2066	601006	80	54	43	7.7 / 11.2	6.1 / 8.9	7480	1210	9540	4.98	65.16	14.7	77	957.85	0	0	2
2066	600624	60	56	43	7.7 / 11.2	6.1 / 8.9	7480	1555	10250	4.30	67.37	17.7	80	1,192.45	1	0	2
2066	600624	80	56	43	7.7 / 11.2	6.1 / 8.9	7480	1555	10230	4.29	67.37	17.7	80	1,192.45	1	0	2
2070	600624	80	56	43	7.7 / 11.2	6.1 / 8.9	7480	1555	10230	4.29	67.37	17.7	80	1,192.45	1	0	2
2076	601000	80	54	43	7.7 / 11.2	6.1 / 8.9	7480	1155	9450	5.76	65.16	12.6	75	821.02	0	0	2
2076	601000	80	54	43	7.7 / 11.2	6.1 / 8.9	7480	1155	9430	5.74	65.16	12.6	75	821.02	0	0	2
2076	601006	80	54	43	7.7 / 11.2	6.1 / 8.9	7480	1210	9560	4.99	65.16	14.7	77	957.85	0	0	2
2076	601006	80	54	43	7.7 / 11.2	6.1 / 8.9	7480	1210	9540	4.98	65.16	14.7	77	957.85	0	0	2
2076	600624	80	56	43	7.7 / 11.2	6.1 / 8.9	7480	1555	10250	4.30	67.37	17.7	80	1,192.45	1	0	2
2076	600624	80	56	43	7.7 / 11.2	6.1 / 8.9	7480	1555	10230	4.29	67.37	17.7	80	1,192.45	1	0	2
2086	600633	80	58	48	7.7 / 11.2	6.1 / 8.9	7860	1570	10640	4.24	70.87	17.7	80	1,254.40	1	0	2
2095	601241	86	63	54.3	6.5 / 11	4.7 / 8	10180	1780	13360	4.88	77.37	17.7	88	1,369.45	1	0	2
2099	601253	86	63	55	6.5 / 11	4.7 / 8	10180	1780	13360	4.82	78.37	17.7	88	1,387.15	1	0	2,7
2105	601241	86	63	54.3	6.5 / 11	4.7 / 8	10180	1780	13360	4.88	77.37	17.7	88	1,369.45	1	0	2
2109	601253	115	63	55	7.5 / 13	5.4 / 9.4	10260	1780	13440	4.84	78.37	17.7	88	1,387.15	1	0	2,7
New Holland																	
LS160	600994	42	54	42.5	7.5 / 0	6.4 / 0	5534	1145	7484	4.63	64.16	12.6	74.5	808.42	0	0	
LS160	600997	42	54	42.5	7.5 / 0	6.4 / 0	5534	1210	7614	4.04	64.16	14.7	76.5	943.15	0	0	
LS170	600994	52	54	42.5	7.5 / 0	6.4 / 0	5540	1145	7490	4.63	64.16	12.6	74.5	808.42	0	0	
LS170	600997	52	54	42.5	7.5 / 0	6.4 / 0	5540	1210	7620	4.04	64.16	14.7	76.5	943.15	0	0	
LS180	600636	67	60	48	7.2 / 11.6	5.7 / 9.2	7193	1600	10033	3.94	71.87	17.7	86	1,272.10	1	0	
LS185B	600636	67	60	48	7.2 / 11.6	5.7 / 9.2	7193	1600	10033	3.94	71.87	17.7	86	1,272.10	1	0	
LS190	600642	83	60	51	7.6 / 12.2	6.1 / 9.7	7860	1600	10700	4.06	74.37	17.7	86	1,316.35	1	0	
LX865	600636	67	60	48	7.2 / 11.6	5.7 / 9.2	7193	1600	10033	3.94	71.87	17.7	86	1,272.10	1	0	
LX885	600636	67	60	48	7.2 / 11.6	5.7 / 9.2	7193	1600	10033	3.94	71.87	17.7	86	1,272.10	1	0	
LX985	600642	83	60	51	7.6 / 12.2	6.1 / 9.7	7860	1600	10700	4.06	74.37	17.7	86	1,316.35	1	0	
Thomas																	
175	600938	56	52	39.5	7.7 / 0	6.1 / 0	3175	1194	5223	3.33	62.16	12.6	75	783.22	0	SN1301-8.0-0	10
175	600979	56	52	39.5	7.7 / 0	6.1 / 0	3175	1249	5333	2.92	62.16	14.7	77	913.75	1	SN1301-8.0-0	10
225 Turbo	600732	87	56	44.8	6.2 / 0	4.9 / 0	8000	1611	10862	4.55	67.37	17.7	80	1,192.45	2	SN2302-8.0-1	8
245 Turbo	600732	87	56	44.8	6.2 / 0	4.9 / 0	8000	1611	10862	4.55	67.37	17.7	80	1,192.45	2	SN2302-8.0-1	8
250	601183	87	59	48.8	6.8 / 12.5	5.4 / 9.9	8000	1646	10932	4.30	71.87	17.7	80	1,272.10	1	SN2302-8.0-1	8
255 Turbo	601183	87	59	48.8	6.8 / 12.5	5.4 / 9.9	8000	1646	10932	4.30	71.87	17.7	80	1,272.10	1	SN2302-8.0-1	8

Loeering Versatile Track Sytem - VTS Specifications

10/17/2007 10:18:28 AM

VTS Part Number)	HP	Track length	Wheel Base (in)	Standard Machine MPH	VTS MPH	Machine Weight	1 side unit weight	Total machine weight with tracks	PSI - Complete loader and Track	Ground Contact length Per Side (in)	Track Width (in)	Overall Machine width with VTS (in)	Ground Contact Area Per Side (sq in)	Up Stop	Spacers	Notes / Additional Hardware	
Trak																	
1750D	600938	86	52	40.1	6.3 / 0	5 / 0	6837	1145	8787	5.61	62.16	12.6	69	783.22	0	0	
1750D	600982	86	52	40.1	6.3 / 0	5 / 0	6837	1256	9009	4.93	62.16	14.7	73	913.75	2	SN2302-8.0-1	9
Volvo																	
MC110	600624	83	56	43.8	6 / 0	4.8 / 0	7645	1611	10507	4.41	67.37	17.7	82	1,192.45	1	SN2302-8.0-1	8
MC70	600938	60	52	40.4	7 / 0	6 / 0	5902	1145	7852	5.01	62.16	12.6	69	783.22	0	0	
MC70	600982	60	52	40.4	7 / 0	6 / 0	5902	1256	8074	4.42	62.16	14.7	73	913.75	2	SN2302-8.0-1	9
MC80	600938	86	52	40.1	6.3 / 0	5 / 0	6837	1145	8787	5.61	62.16	12.6	69	783.22	0	0	
MC80	600982	86	52	40.1	6.3 / 0	5 / 0	6837	1256	9009	4.93	62.16	14.7	73	913.75	2	SN2302-8.0-1	9
MC90	600621	83	56	42.1	6.5 / 0	5.2 / 0	7233	1611	10095	4.30	66.37	17.7	82	1,174.75	1	SN2302-8.0-1	8

- 1: Machine Hose Routing on the side of the Boom needs to be removed
- 2: Modification to Rear Tie Downs may be needed
- 3: No Offset Sprocket Design
- 4: Obsoleted PN - Replaced by New Sales Kit Part Numbers
- 5: This Configuration was never built
- 6: Nut Kit (401206-32)
- 7: Nut Kit (PH0191-2BP-8 (Qty. 4))
- 8: Stud Kit (PI0181-1.63C-32)
- 9: PI0181-1.63C-32
- 10: PI0181-2.25C-8